Explosion Proof Wet/Dry HEPA Vacuum - C1D1/C2D1 - 120V AC, 60Hz - 25 Gal SS Tank - 40' Cord

Part #: EPV-EV-25G-SS-120V-40C-EPP



The Larson Electronics EPV-EV-25G-SS-120V-40C-EPP Explosion Proof Wet/Dry HEPA Vacuum is suitable for use in locations where flammable substances are present or may stand to exist. Compatible with 120V AC, 60 Hz, this spark-free unit provides 133 CFM of vacuum flow with a 25-gallon tank. The explosion proof HEPA vacuum is constructed of 304 stainless steel and comes with 40' of 14-3 cord and explosion proof cord cap for connection to power sources.

The EPV-EV-25G-SS-120V-40C-EPP is an explosion proof electric wet/dry HEPA vacuum for flammable work sites. This 1.3HP unit features a 25-gallon stainless tank and offers compatibility with 120V AC, 60 Hz. Vacuum flow rate is 133 CFM with 70" static water lift. Equipped with a 16gallon dry capacity and 17-gallon wet capacity, the 1,080-watt explosion proof electric vacuum contains a drain valve for quick emptying. Noise levels may reach 75 dBA during use. The HEPA filter that comes with the explosion proof unit features a minimum efficiency of 99.995% at 0.3 microns. Designed for Class I, Division 1 and Class II, Division 1 flammable facilities, the EPV-EV-25G-SS-120V-40C-EPP is constructed of 304 stainless steel.

Click Photos to Enlarge





5-15 Straight Blade Plug

5-20 Straight Blade Plug

Wiring & Plug: This explosion proof electric vacuum is equipped with 40 feet of 14-3 cord that is fitted with an explosion proof cord cap for easy connection to explosion proof outlets. Plug options include a 5-15 15 amp straight blade plug for use with 120V explosion proof outlets or a 5-20 20 amp straight blade plug for use with 120V explosion proof outlets.

PLEASE NOTE Voltage ratings on plugs and outlets are MAXIMUM voltage. For low voltage applications, proper voltage must be applied to the outlet or damage to the unit will occur.

Mounting: The EPV-EV-25G-SS-120V-40C-EPP is mounted on a portable cart for seamless mobility around flammable work sites. Equipped with two locking casters at the front and two wheels at the back, the stainless steel tank is secured on the cart via a circular rail.

Included Accessories: HEPA Filter, Dry Filter, Wet Filter, Tilting Stainless Steel Tank w/ Dump Valve, Anti-static Hose, Double-bend Wand, Stainless Steel Crevice Tool, Dusting Brush w/ Conductive Bristles, Curved-top Nozzle, Floor Tool w/ Brass Wheels, Conductive Bristle Tips and Rubber Squeegee Strip.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

9419 E US HWY 175, Kemp, TX 75143 Phone: 1 800-369-6671 Fax: 903.498.3364 Email: sales@LarsonElectronics.com

Specifications / Additional Information

EPV-EV-25G-SS-120V-40C-EPP Explosion Proof Electric Vacuum

Listing: United States, Canada

Unit Type: Explosion Proof Wet/Dry HEPA Vacuum

Dimensions: 43" x 27" x 27"

Weight: 100 lbs

Voltage: 120V AC, 60 Hz

Watts: 1080W **HP:** 1.3 HP

CFM: 133

Static Water Lift: 70"

Tank Size: 25 Gallons

Filtration Type: HEPA 99.995% @ 0.3 Micron

Dry Capacity: 16 Gallons **Wet Capacity:** 17 Gallons

Hose Size: 10` (1 1/2" OD) - Anti-static Kanaflex

Noise Level: 75 dBA

Motor Type: Electric, Spark-free

Amps: 9A @ 120V

Materials: 304 Stainless Steel Tank, Brass

Mount: Cart w/ (4) Wheels

Wiring: 40` 14-3 Cord w/ EXP Cord Cap

EXP Cord Cap Options: 5-15P or 5-20P

Included Accessories: HEPA Filter, Dry Filter, Wet Filter, Tilting SS Tank w/ Dump Valve, Anti-static Hose, Double-bend Wand, SS Crevice Tool, Dusting Brush w/ Conductive Bristles, Curved-top Nozzle, Floor Tool w/ Brass Wheels, Conductive Bristle Tips, Rubber Squeegee Strip

Scroll Down to Purchase

This product does not qualify for free shipping.

Part #: EPV-EV-25G-SS-120V-40C-EPP (224458)

Ratings

Class I, Division 1 Group D

Class II, Division 1 Groups E,F,G

Wet/Dry Vacuum

Includes Listed Accessories

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: +01-903-498-3364

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Larson Electronics LLC www.LarsonElectronics.com

9419 E US HWY 175, Kemp, TX 75143 Phone: 1 800-369-6671 Fax: 903.498.3364 Email: sales@LarsonElectronics.com

Options:

EPV-EV-25G-SS-120V-40C-EPP- CORD CAP

Example: EPV-EV-25G-SS-120V-40C-EPP-1523

| CORD CAP | |
|----------|------------|
| 5-15 | -1523 |
| 5-20 | -2023-125V |

Larson Electronics LLC www.LarsonElectronics.com

9419 E US HWY 175, Kemp, TX 75143 Phone: 1 800-369-6671 Fax: 903.498.3364 Email: sales@LarsonElectronics.com

Links (Click on the below items to view):

- Hi-Res Image 1- Explosion Proof Wet/Dry HEPA Vacuum