

**1 HP Explosion Proof Motor - Class I, II - 230V 1PH 50 Hz, 1.6 FLA - 1750 RPM - C Face/Foot Mount**

Part #: EXP-MTR-1P-230-50HZ-1HP-1.8K-56C



The Larson Electronics EXP-MTR-1P-230-50HZ-1HP-1.8K-56C Explosion Proof Motor is recommended for use in Class I, Division 1 Groups C, D and Class II, Division 1 Groups F, G rated work sites. The 1 HP unit is compatible with 230V AC single phase 50 Hz and offers 1.6 FLA @ high. This Class F insulation rated explosion proof motor features a NEMA 56 motor and can be installed with industrial systems via an integrated mounting foot and C-face flange.

The EXP-MTR-1P-230-50HZ-1HP-1.8K-56C is a fractional explosion proof motor for flammable work sites. This thermally protected unit operates with 230V AC single phase 50 Hz. The 1 HP motor offers 1.6 full-load amps @ high with 77% full-load efficiency. Capable of generating 1750 RPM, this motor is totally enclosed and fan-cooled (TEFC).

The IP55-rated explosion proof motor features an ambient temperature rating of 50°C. Equipped with aluminum endshields, this unit is protected by a NEMA 56 motor frame and features Class F insulation, with 1.0 service factor.

**Wiring:** The EXP-MTR-1P-230-50HZ-1HP-1.8K-56C comes with a 12" x 12" x 8" NEMA-rated explosion proof box for completing electrical connections.

**Mount:** The EXP-MTR-1P-230-50HZ-1HP-1.8K-56C contains C-face flange and foot mounting components for supporting the motor's weight at both ends. The face of the motor features threaded mounting holes for ease of installation. Feet components are typically fixed on the surface, which reduces unnecessary movements during operation.

**Applications:** Hazardous locations, industrial facilities, pumps, mixers, conveyors, manufacturing, food processing, chemical plants and more. At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

**Specifications / Additional Information****EXP-MTR-1P-230-50HZ-1HP-1.8K-56C Explosion Proof Motor****Motor Dimensions:** 11.92" x 6.92" x 6.98"**Box Dimensions:** 12" x 12" x 8"**Weight:** 27 lbs**Phase:** Single Phase**Voltage:** 230V AC**Frequency:** 50 Hz**Poles:** 2**Output Horsepower:** 1 HP**Kilowatt:** 0.75 KW**Rotations per Minute:** 1750 RPM**Motor Frame:** NEMA 56**Full Load Amps @ High:** 1.6 FLA**FL Efficiency:** 77%**Service Factor:** 1**Insulation:** Class F**Noise:** -**Ambient Temperature Rating:** 50°C**Materials:** Aluminum**Mount:** C Face Flange/Foot Mount**Wiring:** 24" (+2/-0) Leads**Color:** Black**Ratings**

Listed for United States &amp; Canada

Class I, Division 1 Groups C,D

Class II, Division 1 Groups F,G

T3C Temperature Rating

IP55

TEFC Cooling

Aluminum Endshields

**Special Orders- Requirements**

Contact us for special requirements

**Phone:** 1-214-616-6180**Toll Free:** 1-800-369-6671**Fax:** 1-903-498-3364**E-mail:** sales@larsonelectronics.com[Scroll Down to Purchase](#)

This product does not qualify for free shipping.

Part #: EXP-MTR-1P-230-50HZ-1HP-1.8K-56C (223207)

Links (Click on the below items to view):

- [Hi-Res Image 1- Explosion Proof Motor](#)