



Confirmation of Product Type Approval

Please refer to the "Service Restrictions" shown below to determine if Unit Certification is required for this product.

This certificate reflects the information on the product in the ABS Records as of the date and time the certificate is printed.

Pursuant to the Rules of the American Bureau of Shipping (ABS), the manufacturer of the below listed product held a valid Manufacturing Assessment (MA) with expiration date of 15-MAR-2022. The continued validity of the Manufacturing Assessment is dependent on completion of satisfactory audits as required by the ABS Rules.

And; a Product Design Assessment (PDA) valid until subject to continued compliance with the Rules or standards used in the evaluation of the product.

The above entitle the product to be called Product Type Approved.

The Product Design Assessment is valid for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.

ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

Product Name: Cable, Power

**Model Name(s): CBPJP85/SC (VFD), CBPJP86/SC (VFD), CBPJP85/NC (VFD),
CBPJP86/NC (VFD)**

Presented to:

JIANGSU HONEST CABLE CO., LTD.
HEYE XI RU, JIANGYANG INDUSTRY DISTRICT
YANGZHOU, JIANGSU
225008
China

Intended Service:

Power, Lighting and Control System for Shipboard and Offshore Building. Not intended for use as propulsion cable.

Description:

CBPJP85/SC (VFD) - XLPE insulation copper tape shielded copper wire braided cross-linked polyolefin outer sheathed shipboard cable, Type SC. CBPJP86/SC (VFD) - XLPE insulation copper tape shielded copper wire braided thermoplastic polyolefin outer sheathed shipboard cable, Type SC. CBPJP85/NC (VFD) - XLPE insulation copper tape shielded copper wire braided cross-linked polyolefin outer sheathed fire-resisting shipboard cable, Type NC. CBPJP86/NC (VFD) - XLPE insulation copper tape shielded copper wire braided thermoplastic polyolefin outer sheathed fire-resisting shipboard cable, Type NC.

Tier:

3

Ratings:

Type /SC - Halogen-free low-smoke bunched flame retardant cable, comply with IEC60332-3, Cat. A, IEC60754, IEC61034 Type /NC - Halogen-free Low-smoke Low-toxicity fire-resistant cable, comply with IEC60331, IEC60332-3, Cat. A, IEC60754, IEC61034 No. of Cores: Nominal Cross Section mm²: 1,3,4
4,6,10,16,25,35,50,70,95,120,150,185,240 3+3 3*4+3*1.0, 3*6+3*1.0, 3*10+3*1.5, 3*16+3*2.5, 3*25+3*4, 3+3 3*35+3*6, 3*50+3*10, 3*70+3*10, 3*95+3*16, 3*120+3*25, 3+3 3*150+3*25, 3*185+3*35, 3*240+3*35 0.6/1kV, 1.8/3kV,

Maximum Conductor Temperature: 90 Degree/C

Service Restrictions:

Unit Certification is not required for this product. However, unit certification is required for electric propulsion cables. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined. Electrical cables are to be tested by the manufacturers in accordance with the standards of compliance. Records of tests are to be maintained and are to be submitted upon request by ABS. For propulsion cables, see 4-8-5/5.17.11 of Steel Vessel Rules.

Comments:

1.The Manufacturer has provided a declaration about the control of, or the lack of Asbestos in this product. 2.The following cable markings are to be provided in accordance with IEC 60092-353: Indication of origin (manufacturer s name or trade mark) and rated voltage (Uo/ U) and construction (number of cores pairs triples or quads and cross sectional area of the conductor). 3.All propulsion cables, other than internal wiring in control gears and switchboards, are to be subjected to dielectric and insulation tests in the presence of the Surveyor.

Notes / Documentation:

Test Report No.: CT09-1719-1, CT09-1719-2 by China National Centre for Quality Supervision and Test of Electric Wire and Cable, Dated 2 September 2009
Drawing No.: VFD cable dwg, VFD cable dwg by ABS task 875071 dated 28 Mar 2012.

Term of Validity:

This Product Design Assessment (PDA) Certificate 17-SQ1607666-PDA, dated 16/Mar/2017 remains valid until 15/Mar/2022 or until the Rules or specifications used in the assessment are revised (whichever occurs first). This PDA is intended for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product. Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA. Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

ABS Rules:

1-1-4/7.7, 1-1-Appendix 3 and 4, 4-8-3/9, 4-8-3/9.17 and 4-1-1/Table 3 item 20 of Steel Vessel Rules (2017) 1-1-4/9.7, 1-1-Appendix 2, 1-1-Appendix 3, 4-3-4/7.1 of Mobile Offshore Drilling Units Rules (2017) 1-1-4/7.7, 1-1-Appendix 3 and 4, 4-6-4/13 of Steel Vessels Under 90 Meters (295 Feet) in Length (2017) 1-1-4/9.7, 1-1-Appendix 2 and 3, 3-6/13 of Facilities on Offshore Installations (2017) 1-1-4/7.7, 1-1-Appendix 3 and 4, 4-8-3/9 of Offshore Support Vessels (2017) 1-1-4/11.9, 1-1-Appendix 2 and 3, 4-6-4/13 of High-Speed Craft (2017) 1-1-4/7.7, 1-1-Appendix 3 and 4, 4-1-3/9 of Steel Barge Rules (2017)

National Standards:**International Standards:**

IEC 60092-350 (2014), IEC 60092-353 (2011), IEC 60092-360 (2014), IEC 60228 (2004), IEC 60332-3-22 Category A (2009), IEC 60331-1 (2009), IEC 60331-2 (2009)

Government Authority:**EUMED:****Others:****Model Certificate****Model Certificate No****Issue Date****Expiry Date**

PDA

17-SQ1607666-PDA

16-MAR-2017

15-MAR-2022



ABS Programs

ABS has used due diligence in the preparation of this certificate and it represents the information on the product in the ABS Records as of the date and time the certificate was printed. Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. Limited circumstances may allow only Prototype Testing to satisfy Type Approval. The approvals of Drawings and Products remain valid as long as the ABS Rule, to which they were assessed, remains valid. ABS cautions manufacturers to review and maintain compliance with all other specifications to which the product may have been assessed. Further, unless it is specifically indicated in the description of the product; Type Approval does not necessarily waive witnessed inspection or survey procedures (where otherwise required) for products to be used in a vessel, MODU or facility intended to be ABS classed or that is presently in

class with ABS. Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.