

**3/4 HP Explosion Proof Portable Ventilation Exhaust Fan - C1D1/C2D1 - 120V - 2500 CFM - 15'  
Cord w/ EXP Cord Cap  
EPF-VFP-12-120V-NFK-15C-16.3-EPP**



**EPF-VFP-12-120V-NFK-15C-16.3-EPP Explosion Proof Exhaust Fan**

NRTL Listed for United States, Canada

Unit Type: Portable Explosion Proof Ventilation Exhaust Fan

Dimensions: 17.13" x 16.93" x 25.36"

Weight: 36 lbs

Voltage: 120V AC

Startup Amps: 8.6A

Motor: 3/4 HP

RPM: 3600 RPM

CFM: 2500 CFM

Power Factor: 0.76

Noise: 71 dB

Switch: On/off, External

Inlet: 12" (Duct Not Included)

Operating Temperature Range: -

Temperature Rating: T3B

Materials: Non-sparking/Non-metallic (Fan Blades), Steel (Body)

Mount: Portable w/ Carrying Handle, Rubber Feet

Cord: 15' 16/3 SOOW Cord w/ EXP Cord Cap

Cord Cap Options: 5-15P or 5-20P

Color: Safety Orange

**Ratings**

Class I, Divisions 1 & 2 Groups C,D

Class II, Divisions 1 & 2 Groups E,F,G

IP54

Weatherproof Fan

T3B Temp Rating

External Grounding Lug

Duct Not Included

**Special Orders- Requirements**

Contact us for special requirements

Phone: 1-214-616-6180

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

**Options:**

**EPF-VFP-12-120V-NFK-15C-16.3-EPP-Cord Cap**

**Example:** EPF-VFP-12-120V-NFK-15C-16.3-EPP-1523

Cord Cap	
5-15	-1523
5-20	-2023-125V

Links (Click on the below items to view):

- [addpic1large](#)
- [addpic2large](#)
- [addpic3large](#)
- [addpic4large](#)
- [large](#)
- [medium](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)