

Explosion Proof LED Bug Eyes w/ Exit Sign - Class I, II, III - 120-277V - 180 Mins Emergency Runtime - IP65/N4X
EXP-EMG-EXT-3L-6.5W-LED



EXP-EMG-EXT-3L-6.5W-LED Explosion Proof Emergency LED Bug Eyes w/ Exit Sign

Listing: United States, Canada

Lamp Technology: LED

Lamp Qty: (2)

Dimensions: 23.88" x 19.75" x 5.63"

Weight: 40.5 lbs

Voltage: 120-277V AC, 60Hz

Total Watts: 9.66W

Single-lamp Watts: 4.83W

Total Lumens: 841.56 lms

Single-lamp Lumens: 420.78 lms

Luminous Efficacy: 87.12 Lm/W

LED Life Expectancy: 50,000 Hours

Color Temperature: 5672K - White

CRI: 72

Lamp Type: -

Lamp Base: -

Replacement Lamp: -

Beam Angle: -

Lighting Configuration: Spot

Emergency Runtime: 180 Minutes

Battery: NiCad Rechargeable Battery

Safety: Push-to-Test, Pilot Lights

Power Efficiency: -

Power Factor: -

Sign Type: Single Face

Sign Lettering: EXIT (Red)

Amps: 0.08A @ 120V, 0.04A @ 240V, 0.34A @ 277V

Operating Temperature Range: 10°C to 45°C

Temp Rating: T6

Materials: A360 Copper-free Aluminum, Acrylic, Stainless Steel, Neoprene

Finish: Baked-on Gray Epoxy Finish

Mounting: Wall

Hubs: (3) 1" NPT

Ratings

Class I, Division 1 Groups C, D

Class I, Zone 1 Groups IIA, IIB

Class II, Division 1 Groups E, F, G

Class III

NEMA 4X

IP65

Suitable for Wet Locations

Horizontal and Vertical Adjustable

180 Mins Emergency Runtime

Captive, Hinged-access Door

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: +01-903-498-3364

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Links (Click on the below items to view):

- [addpic1large](#)
- [addpic2large](#)
- [addpic3large](#)
- [addpic4large](#)
- [large](#)
- [Manual](#)
- [medium](#)
- [SpecSheet](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)