SupremeRAID[™]SR-1000

S GRAID

SPEC SHEET

Introducing the world's first NVMe and NVMeoF RAID card to unlock the full potential of your SSD performance. GRAID SupremeRAID[™] cutting edge technology eliminates the traditional RAID performance bottleneck to deliver world-record performance, comprehensive data protection, and unmatched flexibility at the lowest TCO on the market.



World-Record Performance

Named one of the Ten Hottest Data Storage Startups of 2021 by CRN, as well as CES 2022 Innovation Award Honoree, GRAID SupremeRAID[™] performance is breaking world records. Contact us today to find out how GRAID's NVMe solution can unlock the full potential of your high performance workloads.

	Linux Environment			Windows Environment		
OPTIMAL	RAID 5	RAID 6	RAID 10	RAID 5	RAID 6	RAID 10
4k Random Read	16 M IOPS	16 M IOPS	16 M IOPS	2 M IOPS	2 M IOPS	2 M IOPS
4k Random Write	820 k IOPS	450 k IOPS	6 M IOPS	500 k IOPS	450 k IOPS	1 M IOPS
1M Sequential Read	110 GB/s	110 GB/s	110 GB/s	65 GB/s	60 GB/s	70 GB/s
1M Sequential Write	11 GB/s	11 GB/s	25 GB/s	9 GB/s	9 GB/s	35 GB/s

REBUILD REBUILD_SPEED=LOW	Linux Environment			Windows Environment		
4k Random Read	3 M IOPS	3 M IOPS	9 M IOPS	350 k IOPS	350 k IOPS	2 M IOPS
4k Random Write	600 k IOPS	400 k IOPS	5 M IOPS	400 k IOPS	370 k IOPS	1 M IOPS
1M Sequential Read	12 GB/s	13 GB/s	55 GB/s	12 GB/s	13 GB/s	15 GB/s
1M Sequential Write	11 GB/s	11 GB/s	25 GB/s	8 GB/s	8 GB/s	13 GB/s

BASED ON TESTING SPECIFICATIONS LISTED ON SIDE 2

BASED ON TESTING SPECIFICATIONS LISTED ON SIDE 2

Contact Us Now

CALL 1 (866) GRAID-10 EMAIL info@graidtech.com WEB graidtech.com DOWNLOAD THE BROCHUREDOWNLOAD THE USER GUIDE

READ THE WHITEPAPERS

● DOWNLOAD THE USER GUIDE



SupremeRAID[™]SR-1000

SPEC SHEET

Test Environment Specifications Software: Linux Version: CentOS 8.5; Windows Version: Windows Server 2019 | **Hardware:** CPU: Intel(R) Xeon(R) Gold 6338 CPU 32-Core with 2.0GHz x 2; Memory: SK Hynix HMA82GR7CJR8N-XN DIMM DDR4 3200 MHz 16GB x 16; SSD: INTEL D7-P5510 SSDPF2KX038TZ 3.8TB x 20 | **RAID Configuration:** Random performance based on a drive group with 12 physical drives and 1 virtual drive; sequential performance based on a drive group with 20 physical drives and 1 virtual drive





SR-1000 Software Specs

Supported RAID levels	RAID 0, 1, 5, 6, 10
Max Physical Drives	32
Max Drive Groups	4
Max Virtual Drives per Drive Group	8
Max Drive Group Size	Defined by physical drive size
OS Support	Linux: CentOS 7.9, 8.4, 8.5 openSUSE Leap 15.2, 15.3 RHEL 8.4, 8.5 SLES 15 SP2, SP3 Ubuntu 20.04 Windows Server 2019 x86-64 Windows 10 x86-64

SR-100 Card Specs

Host Interface	x16 PCle Gen 3.0
Max Power Consumption	50 W
Form Factor	2.713" H x 6.137" L, Single Slot
Product Weight	132.6 g

\oslash

Flexible & Future Ready

Unmatched flexibility with features like new O/S support, compression, encryption, thin provisioning, or boot drive protection can be easily added with software releases



World Record Performance

Full NVMe performance with a single card: 16M IOPS and 110GB/s throughput based on RAID5 with 3rd Generation Intel® Xeon Scalable Platform and Intel D7-P5510



Highly Scalable

Easily manage 32 direct attached NVMe SSDs; extend data protection without sacrificing performance with Software Composable Infrastructure



Plug & Play

Effortless installation, no cabling or motherboard re-layout required; direct connect to SSD without PCle switches



Free Up CPU Resources

Offload your entire RAID computation to the GRAID card to free-up CPU computing resources for 5G, AI, and AIoT applications



Easy to Use

GRAID SupremeRAID[®] doesn't rely on memory caching technology, eliminating the need for battery backup modules

Contact Us Now

CALL1 (866) GRAID-10EMAILinfo@graidtech.comWEBgraidtech.com

DOWNLOAD THE BROCHURE
DOWNLOAD THE USER GUIDE
READ THE WHITEPAPERS

③ DOWNLOAD THE BROCHURE

