7.5 kVA Isolation Transformer - 240V Primary - 24V AC Secondary -50/60Hz - Fully Potted/Encapsulated Part #: MT-ISX-FP-1P-240V-7.5KVA-24V-N3R



The MT-ISX-FP-1P-240V-7.5KVA-24V-N3R Single Phase Isolation Transformer from Larson Electronics is powerful, reliable, and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-FP-1P-240V-7.5KVA-24V-N3R provides increased reliability, higher efficiency, protection against critical equipment failures and an extra level of protection by isolating the power source from the connected device. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: The MT-ISX-FP-1P-240V-7.5KVA-24V-N3R isolation transformer is a single phase unit with a 7.5 kVA rating and a primary voltage of 240 V AC on the primary side. This transformer has a secondary voltage of 24 V AC on the secondary side. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology. This unit's primary and secondary windings are separated, allowing operators to connect the primary and secondary components to form an autotransformer. When the primary and secondary windings are connected, the unit is no longer an isolated transformer and becomes a buckboost transformer (autotransformer).

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The NEMA 3R painted steel enclosure makes the unit suitable for both indoor and outdoor applications, and this step-down transformer can be either floor or wall mounted. The MT-ISX-FP-1P-240V-7.5KVA-24V-N3R features a 180°C insulation with a 135°C temperature rise.

Construction: The aluminum winding in the MT-ISX-FP-1P-240V-7.5KVA-24V-N3R are formed from high quality aluminum wire help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. Isolation transformers are designed to maximize the performance and life of electrical equipment. The MT-ISX-FP-1P-240V-7.5KVA-24V-N3R is encapsulated in silica sand and resin, and cased in a NEMA 3R steel enclosure. NEMA 4, NEMA 4X, and NEMA 12 enclosures are available upon request.

Benefits: The MT-ISX-FP-1P-240V-7.5KVA-24V-N3R isolation transformer offers many benefits to the consumer. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Installation and maintenance costs are reduced due to the smaller form factor, and less overall space requiorments are decreased. In addition, these transformers operate quieter than a standard autotransformer of the same capacity.

Mounting: Integrated wall mounting brackets make installation fast and easy. Because of the smaller overall footprint, heavy machinery is rarely needed for mounting and installation.

Applications: Air conditioners, lighting systems, heating elements, motor applications and other applications that that require the ability to power loads that differ from the available line voltage.

Limitations: While there are many benefits to an isolation transformer and there are some limitations to consider. This transformer will only transform voltage, it will not convert phases and does not allow use of the neutral. If any of these limitations apply to you, you will need a standard transformer. Please see below link for our standard line of industrial transformers or our line of phase converters.

Note on Phases: For three phase transformers, click on the following links:

Three Phase Delta Buck/Boost Transformers

Three Phase Wye Buck/Boost Transformers

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Specifications / Additional Information

MT-ISX-FP-1P-240V-7.5KVA-24V-N3R Isolation Transformer	Ratings
Transformer Type: Isolation Transformer	UL listed for United States
Transformer Configuration: Buck	CSA certified for Canada
Phase: Single Phase	NEMA 3R Indoor/Outdoor Enclosure
Frequency: 50/60 Hz	Meets or Exceeds NEMA ST-20 Standards
Primary Voltage: 240 V AC	Isolation Transformer
kVA: 7.5 kVA	Fully Potted/Encapsulated
Phase: Single Phase Frequency: 50/60 Hz Primary Voltage: 240 V AC	NEMA 3R Indoor/Outdoor Enclosure Meets or Exceeds NEMA ST-20 Standards Isolation Transformer

Secondary Voltage: 24 V AC Winding Material: Aluminum Knockouts: Side and Rear Primary Termination: Front Access Copper Tabs or Lead Wires Secondary Termination: Front Access Copper Tabs or Lead Wires Cooling: Air / Dry Type Insulation: 180°C Temperature Rise: 135°C Temp Rating: 30°C Enclosure Rating: NEMA 3R Encapsulation: Silica Sand, Resin Compounds Enclosure Material: Steel **Special Orders- Requirements** Finish: ANSI 61 Grey / UL50 Contact us for special requirements Mounting: Wall Mount via Mounting Tabs Toll Free: 1-800-369-6671 Dimensions: 16.12"H x 13.5"W x 8.55"D Intl: 1-214-616-6180 Weight: 144 lb E-mail: sales@larsonelectronics.com -Scroll Down to Purchase-

This product does not qualify for free shipping.

Part #: MT-ISX-FP-1P-240V-7.5KVA-24V-N3R (224216)

Links (Click on the below items to view):

- Hi-Res Image 1- Isolation Transformer
- Hi-Res Image 2- Isolation Transformer
- Hi-Res Image 3- Isolation Transformer
- Hi-Res Image 4- Isolation Transformer