

24W Explosion Proof POE Injector - Adds Power Over Ethernet Functionality to 24V POE Equipment - 1A

EXP-IP-POE-INJ-24V-24W



EXP-IP-POE-INJ-24V-24W Explosion Proof POE Injector

Device Type: Explosion Proof POE Injector

External Dimensions: 4-17/32"H x 6-1/8"W

Internal Dimensions: 3-3/32"H x 4-1/4"ID

Internal Volume: 31 cu. in.

Weight: 4 lbs

Cover Material: Copper-free Aluminum Alloy

Allen Head Cover Screw Material: Cadmium Plated Steel

Sealing Gasket: Neoprene O-ring

Ground Screw Material: Zinc Plated Steel w/ Green Dye

Enclosure Finish: Silver Powder Epoxy Paint, Electrostatically Applied

Watts: 24W

Voltage: 24V

Max Amp Rating: 1

Cast-in Mounting Pad Configuration: X

Design: Single Cover Box Only

Wiring Hubs: Offset Feed-thru (3/4" NPT)

Wiring: 10` 16/3 SOOW w/ Explosion Proof Cord Cap

Cord Cap Options: 5-15P, 5-20P or 6-20P

Ratings/Approvals

Listed for United States, Canada, Europe, Asia

Class I, Div. 1 & 2, Groups A, B, C, D

Class I, Zones 1 & 2, Groups IIB+H2, IIA

Class II, Div. 1 & 2, Groups E, F, G

Class III, Div. 1 & 2

NEMA Type 3, 4, 4X, 7 (B,C,D), 9 (E,F,G)

ATEX Ex II 2 G / D

IECEX db IIC Gb

IECEX tb IIC Db IP66

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Options:

EXP-IP-POE-INJ-24V-24W-Cord Cap

Example: EXP-IP-POE-INJ-24V-24W-1523

Cord Cap	
5-15P	-1523
5-20P	-2023-125V
6-20P	-2023-250V

Links (Click on the below items to view):

- [Addpic1large](#)
- [Addpic2large](#)
- [large](#)
- [medium](#)
- [SpecSheetSpanish](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)