



MODALIXX G202MDL

Product Features

- 20.1" Gray Scale Application LED Lit
- Changes all Analog signals to High Definition (HD)
- Accepts any signal from 525 to 1600 lines
- Wide viewing angles
- High 1200 cd/m² optimum
- 1500:1 contrast ratio
- Swift 25 ms response time
- User-friendly OSD
- Low power consumption
- AC 100 / 240 V (50 / 60 Hz)
- Durable aluminium and magnesium alloy housing

LCD MODULE	
Type	TFT LCD / LED Lit
Resolution	UXGA 1600 x 1200
Input Resolution	H: 640 - 1920 V: 525 - 1200
Screen Size	20.1"
Brightness	1200 cd/m ²
Contrast Ratio	1500:1
Pixel Pitch	0.255 mm
Response Time	25ms (GTG)
Viewing Angle	170° / 170° (Typical)
Input Connectors	DVI-D 1-5 BNC (Accepts All Configurations)
Video Support	Analog/digital Interfaced and Progressive Video
Termination Switch	75 Ω On/Off
Remote Control	1/8 Phono Jack Socket
Surface Treatment	Hard Coating (2H), Anti-glare Treatment
Scanning Frequency	(H) 15.7 - 90 kHz (V) 50 - 120 Hz
LCD MODULE	
Power	100 - 240 V, (50 / 60 Hz) <70W (On) <4W (Stand-by) <2W (Off)
PHYSICAL PROPERTIES	
Unit Weight	10.8 kg (23.8 lbs)
Dimensions	487 x 398 x 68 mm (W x H x D)
Shipping Dimensions	23" x 23" x 12" (L x W x H) 58.42 x 58.42 x 30.48
Power Socket Connector	3-Pin AC Medical Plug

