

# UHD Pro70 Series

Designed for Mission Critical, Command & Control Environments



**Automatic calibration** features extend the life of the display.  
**Wide RGB color gamut** crucial for intelligence and surveillance.  
Purpose-designed features for **optimal operator experience**.



(260) 494-1499  
neoti.com

910 W. Lancaster St., Bluffton, IN 46714  
sales@neoti.com | service@neoti.com



## UHD PRO70

# SERIES SPECIFICATIONS

REPLACES 70" CUBE DISPLAYS

**0.8**  
Pixel Pitch

**FULL HD**  
1920x1080 px

**Front**  
Install & Service



Optional:



Product Specs		
DISPLAY PROPERTIES	Resolution	1,920 x 1,080 px
	Brightness	700 nits
	Scan Rate	1/60
	Refresh Rate	3840 Hz
	Aspect Ratio	16:9 (1.78)
	Total Pixels	2,073,600
ENGINEERING	Total Panel Weight	80 lbs
	Panel Dimensions	5' 1.02" x 2' 10.33" (61.02" x 34.33")
	Diagonal	70"
	SQM	1.35
	Total Max Power	556 W
	Total Average Power	184 W
	120V/20A Circuits Required	1
	Max Panels Per Circuit	3
	Max BTU/hr	1,898

Specifications are accurate at time of printing. Actual specifications may vary due to customizations or updates. Specifications should be confirmed upon ordering



(260) 494-1499  
NEOTI.COM

910 W. LANCASTER ST., BLUFFTON, IN 46714  
SALES@NEOTI.COM | SERVICE@NEOTI.COM